

LifeWindow™ One

Veterinary Multi-Parameter Physiologic Monitor

*Superior Veterinary Monitoring
Meets Portability*



Gold standard veterinary measurements

- 3/5 Lead Digicare™ VetECG™
- Masimo® SET® Rainbow® oximetry with PVI®
- Capnography with optional Anesthetic Agents
- SunTech® VetBP® Blood Pressure
- Temperature
- Up to 8 hours battery life

*Driven by Innovation ...
... in Veterinary Medicine*
www.digi-vet.com



LifeWindow™ One

Veterinary Multi-Parameter Physiologic Monitor

Digicare's new LifeWindow™ One is a portable veterinary specific physiological monitor with distinctive features and benefits. Engineered with premium veterinary specific modules including an easily operated touch screen user interface. This monitor is in a class of its own, compact and weighing only 3 Lbs. Made with convenience in mind, the LifeWindow™ One can be easily mounted on a rolling stand or IV pole. The perfect combination of size and functionality to complement any hospital (clinic) setting.



All monitors ordered with only 1 parameter will include a plug & play connector for either Masimo CO2 or SpO2 for upgrade at any time. All models come standard with a port to measure temperature. Select up to any 2 parameters of your choice see chart below.

	Code	Module Name	Internal	Plug & Play
ECG	E	3/5 Lead Digicare™ VetECG™	✓	
SpO2	Sm	Masimo® SET® Rainbow® SpO2	✓	
	Sp	Masimo® SET® SpO2		✓
	Sh	Nonin® SpO2	✓	
	Sn	Nellcor® OxiMax®	✓	
GAS	Cmi*/Cme**	Masimo® Side-Stream Capnography	✓	✓
	Gmi*/Gme**	Masimo® Side-Stream Anesthetic Agents	✓	✓
	Mme**	Masimo® Main-Stream Capnography	✓	✓
	Mgme**	Masimo® Main-Stream Anesthetic Agents		✓
	Cri*/Cre**	Respironics® Side-Stream Capnography	✓	✓
	Mre**	Respironics® Main-Stream Capnography		✓
NIBP	N	Suntech® VetBP® Non-Invasive Blood Pressure	✓	
Temp	T	Temperature	✓	
Port	PP3RM	Dual Monitors only additional port for plug & play Respironics CO2 and/or Masimo CO2/SpO2		✓

* Internal Module ** External Module

Part # example of LW One with CO2 Plug & Play Masimo Mainstream, NIBP and temperature port: LW ONE MmN

General Specifications

Display Type - 480x272 4.8" LED backlit TFT screen

Mains Voltage - Automatic Selection 100Vac to 240Vac (50/60 Hz)

Battery - Internal Li-ion rechargeable battery


Relative Humidity - 30 to 70% (non condensing)

Dimensions - W 9.14"(232) H 3.46"(88) D 5.67"(144) (mm)

Weight - 3 Lbs (1.4 Kg)

Safety - Meets IEC601-1-1 and IEC 601-1-2

Driven by Innovation in Veterinary Medicine



DIGICARE
Animal Health
WWW.DIGI-VET.COM

Digicare Animal Health
107 Commerce Road
Boynton Beach, Florida, 33426
USA
Phone: 561-689-0408
Fax: 561-689-0021



Distributed by:

VBS DIRECT Ltd.
Unit 5/6 Whitchurch Industrial Estate,
Shakespeare Way, Whitchurch,
Shropshire, SY13 1LJ
Tel: 0845 5280336
Fax: 0845 5280358

VBS DIRECT
innovative solutions for professionals
For more information go to:
WWW.VBSDIRECT.CO.UK
email: info@vbsdirect.co.uk
0845 5280336